

2-080.02 Swinghandle RS PrC

SOFTLINE



Swinghandle-SOFTLINE for 1-, 2- or 3-point locking systems.

- The Swinghandle can be locked with 40mm long Profile Cylinders (DIN 18252), cylinder or insert.
- This Swinghandle is available with two different sliding dustcovers, enabling the locking with modern Profile Cylinders having a protruding key-barrel part (refer to chart).
- RH or LH application.
- For IP65 applications the lower part of the handle is fixed with a sealed cap.
- For non IP65 applications e.g. page 04.30 the lower part has a fastening hook.

• Detailed dimensions of the cutout PrC see page 04.5.

Material:

- a), a1), b), b1), d), d1), e), e1)
- **Swinghandle:** PA, black
- **Dish:** PA, black
- **Sliding cover:** PA, black
- h)
- **Grounding/Earthing clip:** stainless steel AISI 304



For tailored rods e.g. 201-9006-xxxx on product system 1-180 the length L-in case of symmetrical doors (as drawn) is:

$$L = \frac{\text{upper rod clearance} - 12\text{mm} (0.472)}{2 (0.079)} - 50\text{mm} (1.969)$$

$$L = \frac{\text{lower rod clearance} - 12\text{mm} (0.472)}{2 (0.079)} + 50\text{mm} (1.969)$$

For tailored rods e.g. 201-9006-xxxx on product system 1-180 the length L-in case of rod control at the door center is:

$$L = \frac{\text{clearance} - 12\text{mm} (0.472)}{2 (0.079)}$$

Swinghandle SOFTLINE for Profile Cylinder 40mm long, up to 2.5mm protruding key-barrel part	Part No.	see page
a) for installation with cap (IP65)	107-9005	
b) dish with hook (IP65 not possible)	107-9007	
Swinghandle SOFTLINE for profile cylinder 40mm long, , with raised sliding cover for up to 5mm protruding key-barrel part		
a1) for installation with cap (IP65)	107-9006	
b1) dish with hook (IP65 not possible)	107-9008	
c) Profile Cylinder according DIN 18252		03.34
d) Swinghandle SOFTLINE with fitted cylinder barrel for installation with cap(IP65)		
keyed alike DIRAK 1333*	107-9018	
keyed alike DS200*	507-9210	
keyed different/mixed	107-9020	
d1) as d), but dish with hook (no IP65 rating)		
keyed alike DIRAK 1333*	107-9021	
keyed alike DS200*	507-9211	
keyed different/mixed	107-9023	
Swinghandle SOFTLINE for insert		
e) for installation with cap (IP65)	107-9024	
e1) dish with hook (IP65 not possible)	107-9025	
f) Inserts must be ordered separately		03.36
Locking stub is included in handle-assembly.		
g) Assembling of inserts	207-0016	
Accessories d) to g).		03.16
Cams for 1-point latching		02.58
h) Grounding/Earthing clip:	208-1201.04	04.40

* with stainless dust-shutter

2-080.02 Swinghandle RS PrC

SOFTLINE

