

2-100.02 Swinghandle RS 130



Low Profile Swinghandle for sheet metal and plastic enclosures.

- RH or LH application.
- The polyamide handle is fully insulated.
- The handle is locked by a Profile Cylinder according to DIN 18252 or a KABA Ø22 (0.866) round cylinder.
- Water- and dust-tight according to IP65 DIN EN 60529.

Material:

- a), b) and c) zinc die, black or PA black
- d) and d1)
- **3- and 2-point cam:** steel, zinc plated
- e)
- **Round rods:** steel, zinc plated
- f)
- **Adapter:** zinc die, untreated
- g)
- **Rod Guide:** PA, black



		Cutout 130/Ø46	Cutout 130/□46	see page
a) Swinghandle, PA (black) for profile cylinder 40mm long		207-9001	207-9311	
a1) as a), but with cylinder dustcover		207-9002	207-9312	
a2) Swinghandle, zinc die (black coated) for profile cylinder 40mm long		207-9008	-	
a3) as a2), but with cylinder dustcover		207-9009	-	
a4) as a1), but 5mm raised for profile cylinder 45mm long		207-9003	207-9313	
a5) as a4), but Swinghandle, zinc die (black coated), door dish, PA black for profile cylinders 45mm long		207-9004	207-9314	
b) Swinghandle for round Ø 22 KABA cylinder on request				
c) Swinghandle, PA (black) with padlock device (AISI 304)		207-9006	on request	
Optional:				
d) 3-point-cam e.g. for bending	A20	207-9522	207-9522	03.37
	A26	207-9528	207-9528	
d1) 2-point-cam		207-9599	207-9599	
e) Round rod				02.75, 02.76
f) Adapter for round rod		200-9601	200-9601	
g) Rod guide for bending	A20	200-3601.03	200-3601.03	02.77
Rod guide for bending	A26	200-3602.03	200-3602.03	
h) Profile Cylinder according DIN 18252				03.34
i) KABA cylinder Ø 22 round cylinder on request				
k) Adapter ring to allow installation into 2 holes Ø 46 or □ 46. In this case the same door can be used RH or LH.		207-2701.03	207-2701.03	
k1) External seal for adapter		207-2804	207-2803	

