

## 2-100.01 Swinghandle RS 105



Low Profile Swinghandle for sheet metal and plastic enclosures.

- RH or LH application.
- The polyamide handle is fully insulated.
- The handle is locked by a Profile Cylinder according to DIN 18252 or a KABA Ø22 (0.866) round cylinder.
- Water- and dust-tight according to IP65 DIN EN 60529.

**Material:**

- a), b) and c)  
PA, black or grey RAL 7032
- d) and d1)  
• **3- and 2-point-cam**  
steel, zinc plated
- e)  
• **Round rods:**  
steel, zinc plated
- f)  
• **Adapter:**  
zinc die, untreated
- g)  
• **Rod Guide:**  
PA, black



		Cutout 105/Ø46	see page
a) Swinghandle, PA (black) for profile cylinder 40mm long		207-9101	
a1) as a), but with cylinder dustcover		207-9102	
a2) as a1), but 5mm raised for profile cylinder 45mm long		207-9103	
<b>b) Swinghandle for Ø 22 KABA cylinder</b>			
PA black		207-9109	
PA grey RAL 7032		207-7080*	
<b>b1) as b), but with lead sealable cylinder dustcover</b>			
PA black		207-9110	
PA grey RAL 7032		207-7043*	
<b>b2) as b1), but with reinforced cylinder dustcover</b>			
PA black		207-9111	
PA grey RAL 7032		207-7081*	
<b>c) Swinghandle, PA (black) with padlock device (AISI 304)</b>			
		207-9112	
<b>Optional:</b>			
d) 3-point-cam e.g. for bending	A20	207-9522	03.37
	A26	207-9528	
d1) 2-point-cam		207-9599	
<b>e) Round rod</b>			
<b>f) Adapter for round rods</b>			
		200-9601	
<b>g) Rod guide for bending</b>			
Rod guide for bending	A20	200-3601.03	02.77
Rod guide for bending	A26	200-3602.03	
<b>h) Profile cylinder according DIN 18252</b>			
			03.34
<b>i) KABA cylinder Ø 22 round cylinder on request</b>			
<b>k) Adapter ring allow installation into 2 holes Ø46. In this case the same door can be used RH or LH.</b>			
		207-2701.03	
<b>k1) External seal for adapter</b>			
		207-2804	

\* Quantity and delivery time on request.

### 2-100.01 Swinghandle RS 105

