

7-030 Rod-Latch FS PrA

stainless steel AISI 316



Rod-Latch system for application within the sealed area.

- The latch can be used with escutcheon, handles or Swinghandles.
- RH or LH application.
- Detailed dimensions of the cutout PrA see page 04.5.

Material:

- **Latch, rod, insert, escutcheon, cam, adapter, rod and grounding/earthing device:**
stainless steel
- **Ramp shoe:**
PA, black



	Part No.	see page
a) Rod latch	208-9025	
b) Insert with screw and wave washer		
Square 7	208-9218	
Square 8	208-9219	
Double bit 3 pin	208-9220	
Double bit 5 pin	208-9221*	
Triangular 7	208-9222*	
For handles stainless steel		10.31
c) Escutcheon	208-9304	
d) Cam		
A in mm / inch		
22 / 0.866	200-0518	
24 / 0.945	200-0520	
26 / 1.024	200-0522	
28 / 1.102	200-0524	
30 / 1.181	200-0526	
32 / 1.260	200-0528	
36 / 1.417	200-0532	
54 / 2.126	200-0550	
e) Adapter with screw	208-9406	
f) For rod with ramp shoe		10.37
Round rod		10.12, 10.38
Optional:		
g) Grounding/Earthing clip:	208-1201.04	04.40
Water and dust tight according to IP65 by:		
h) O-ring for insert	208-1801	
i) O-ring	208-1802	
j) e.g. Clip-on profile	209-0201	07.19

* Quantity and delivery time on request.

7-030 Rod-Latch FS PrA

stainless steel AISI 316

