



1-400 3-Point Latch

for Quarter-Turn Cutout

a) Rod-Latch for Round Rod Ø8mm	Stroke 13	Stroke 18	see page
RH version	235-9001	235-9003	
LH	235-9002	235-9004	
a1) Rod-latch for round rod threaded M8			
RH	235-9005	235-9007	
LH	235-9006	235-9008	
b) Latch support for RH and LH version			
A20	235-1001	235-1001	
A26	235-1002	235-1002	
c) Insert with screw M6x10			
Square 6	235-9101	235-9101	
Square 7	235-9102	235-9102	
Square 8	235-9103	235-9103	
Triangular 6,5 CNOMO	235-9104	235-9104	
Triangular 7	235-9105	235-9105	
Triangular 8	235-9106	235-9106	
Double bit 3 pin	235-9107	235-9107	
Double bit 5 pin	235-9108	235-9108	
Daimler Benz	235-9109	235-9109	
d) Escutcheon for double bit only			
A20	235-9201	235-9201	
A26	235-9202	235-9202	
d1) Escutcheon for all other insert variations			
A20	235-9203	235-9203	
A26	235-9204	235-9204	
e) Rod Guide for bending A20	200-3601.03	200-3601.03	02.77
Rod Guide for bending A26	200-3602.03	200-3602.03	
f) Round rods with rollers, to be cut			02.75
L in mm	400	201-9001	201-9001
	500	201-9020-0500	201-9020-0500
	600	201-9002	201-9002
	700	201-9020-0700	201-9020-0700
	800	201-9003	201-9003
	900	201-9020-0900	201-9020-0900
	1000	201-9004	201-9004
	1100	201-9020-1100	201-9020-1100
	1200	201-9005	201-9005
Customized lengths			02.76
f1) Round rods Ø8mm threaded M8. Length L=1000	201-0801-1000	201-0801-1000	
Optional:			
Water- and dust-tight according to IP65 by:			
g) O-Ring	200-1001	200-1001	
h) Flat external seal	200-0901	200-0901	
i) Swinghandle			03.21
j) T- and L-Handle			02.74