

2-080.01 Swinghandle RS PrB

SOFTLINE



Swinghandle-SOFTLINE for 1-, 2- or 3-point locking systems.

- The Swinghandle can be locked with 40mm long Profile Cylinders (DIN 18252), cylinder or insert. Cylinder cam on 45° or 90°.
- This Swinghandle is available with two different sliding dustcovers, enabling the locking with modern Profile Cylinders having a protruding key-barrel part (refer to chart).
- RH or LH application.
- For IP65 applications the lower part of the handle is fixed with a sealed cap.
- For non IP65 applications e.g. page 04.30 the lower part has a fastening hook.

- Detailed dimensions of the cutout PrB see page 04.5.

Material:

- a), a1), b), b1), d), d1), e), e1)
- **Swinghandle:** PA, black
- **Dish:** PA, black
- **Sliding cover:** PA, black h)
- **Grounding/Earthing clip:** stainless steel AISI 304



For tailored rods e.g. 201-9006-xxxx on product system 1-180 the length L-in case of symmetrical doors (as drawn) is:

$$L = \frac{\text{upper rod clearance} - 12\text{mm (0.472)}}{2(0.079)} - 38\text{mm (1.496)} \qquad L = \frac{\text{lower rod clearance} - 12\text{mm (0.472)}}{2(0.079)} + 38\text{mm (1.496)}$$

For tailored rods e.g. 201-9006-xxxx on product system 1-180 the length L-in case of rod control at the door center is:

$$L = \frac{\text{clearance} - 12\text{mm (0.472)}}{2(0.079)}$$

Swinghandle SOFTLINE for Profile Cylinder 40mm long, up to 2.5mm protruding key-barrel part	Part No.	see page
a) for installation with cap (IP65)	407-9055	
b) dish with hook (IP65 not possible)	407-9045	
Swinghandle SOFTLINE for profile cylinder 40mm long, with raised sliding cover for up to 5mm protruding key-barrel part		
a1) for installation with cap (IP65)	407-9056	
b1) dish with hook (IP65 not possible)	407-9046	
c) Profile Cylinder according DIN 18252		03.34
d) Swinghandle SOFTLINE with fitted cylinder barrel for installation with cap (IP65)		
keyed alike DIRAK 1333*	407-9053	
keyed alike DS200*	507-9268	
keyed different/mixed	407-9054	
d1) as d), but dish with hook (no IP65 rating)		
keyed alike DIRAK 1333*	407-9043	
keyed alike DS200*	507-9265	
keyed different/mixed	407-9044	
Swinghandle SOFTLINE for insert		
e) for installation with cap (IP65)	407-9057	
e1) dish with hook (IP65 not possible)	407-9047	
f) Inserts must be ordered separately		03.36
Locking stub is included in handle-assembly.		
g) Assembling of inserts	207-0016	
Accessories d) to g).		03.16
Cams for 1-point latching		02.58
h) Grounding/Earthing clip:	208-1201.04	04.40
* with stainless dust-shutter		

2-080.01 Swinghandle RS PrB

SOFTLINE

