

3/4 extension ball-bearing slide (2 pieces), front disconnect

LG = slide length
 K = travel length
 CN = load rating (kg/pair)



| K | LG | A | B | C | D | E | F | G | CN | part number | material | finish | weight |
|-------|-------|-------|-------|-------|-------|-------|-------|-------|----|-------------|---------------------|--------|--------|
| 228.6 | 304.8 | - | 152.4 | 254 | - | 149.2 | 260.3 | 273 | 49 | 21-7-3576 | 304 stainless steel | raw | 300g |
| 279.4 | 355.6 | - | 203.2 | 304.8 | - | 200 | 311.1 | 323.8 | 47 | 21-7-3577 | 304 stainless steel | raw | 360g |
| 304.8 | 406.4 | - | 254 | 359.6 | - | 250.8 | 361.9 | 374.6 | 43 | 21-7-3562 | 304 stainless steel | raw | 420g |
| 330.2 | 457.2 | 203.2 | 304.8 | 406.4 | 212.7 | 301.6 | 412.7 | 425.4 | 41 | 21-7-3563 | 304 stainless steel | raw | 460g |
| 382 | 508 | 228.6 | 355.6 | 457.2 | 238.1 | 352.4 | 463.5 | 476.2 | 37 | 21-7-3564 | 304 stainless steel | raw | 490g |
| 406.4 | 558.8 | 254 | 406.4 | 508 | 263.5 | 403.2 | 514.3 | 527 | 34 | 21-7-3565 | 304 stainless steel | raw | 560g |
| 432.8 | 609.6 | 279.4 | 457.2 | 558.8 | 288.9 | 454 | 565.1 | 577.8 | 30 | 21-7-3566 | 304 stainless steel | raw | 590g |
| 482.6 | 660.4 | 304.8 | 508 | 609.6 | 314.3 | 504.8 | 615.9 | 628.6 | 27 | 21-7-3567 | 304 stainless steel | raw | 660g |
| 508 | 711.2 | 330.2 | 558.8 | 660.4 | 339.7 | 555.6 | 666.7 | 679.4 | 25 | 21-7-3568 | 304 stainless steel | raw | 690g |

