

Rolled knuckle continuous hinge 57mm open

new!

Opening angle 270°. Other lengths and pin materials are available on request.
 Specific drilling requirements are also available on request.
 Hinge in raw galvanised steel is made of pregalvanised steel.
 Therefore any cut surface is ungalvanised.



A	B	C	D	E	note	material	finish	part number	pin material	weight
2160	57	1.5	4	15	undrilled	galvanised steel	raw	40-1-4680	brass	2000g
2160	57	2	6	30	undrilled	galvanised steel	raw	40-1-4682	brass	2970g
2160	57	1.5	4	15	undrilled	304 stainless steel	raw	42-1-4220	stainless steel	2000g

Rolled knuckle continuous hinge 60mm open

Opening angle 270°. Other lengths and pin materials are available on request.
 Specific drilling requirements are also available on request.

A	B	C	D	E	F	G	S	note	material	finish	part number	pin material	weight
2000	60	1.5	5	40				undrilled	steel	raw	40-1-3541	steel	1980g
2000	60	1.5	8	40				undrilled	steel	raw	40-1-3335	steel	2600g
2040	60	2	6	30				undrilled	steel	raw	40-1-4371	steel	2800g
2000	60	2	6	30				undrilled	5754 alu	raw	41-1-3523	alu	998g
2040	60	2	6	30				undrilled	304 stainless steel	raw	42-1-3302	stainless steel	2800g
2040	60	2	6	30	35	60	4	drilled	304 stainless steel	raw	42-1-4201	stainless steel	2800g
2040	60	2	6	30				undrilled	316 stainless steel	raw	42-1-4002	stainless steel	2800g

Rolled knuckle continuous hinge 63mm open

new!

Opening angle 270°. Other lengths and pin materials are available on request.
 Specific drilling requirements are also available on request.

A	B	C	D	E	note	material	finish	part number	pin material	weight
1800	63	1.5	4	15	undrilled	304 stainless steel	raw	42-1-4221	stainless steel	1800g

