

Buy on-line at the FA Parkes sales portal www.faparkes.co.uk - your one stop shop!

Product datasheet

F.A. Parkes (M.B.F) Limited Unit 4, Acorn Court Butts Street, Leigh Lancashire WN7 3AE Tel. 01942 681 996 sales@faparkes.co.uk

Rolled knuckle continuous hinge 70mm open

Opening angle 270°. Other lengths and pin materials are available on request. Specific drilling requirements are also available on request.

Δ	В	С	D	F	note	material	finish	part number	pin material	weight
2040	70	2	6	30	undrilled	steel	raw	40-1-4372	steel	3114g
1800	70	1.5	4	15	undrilled	304 stainless steel	raw	42-1-4097	stainless steel	1900g
2040	70	2	6	30	undrilled	304 stainless steel	raw	42-1-3859	stainless steel	3120g



Rolled knuckle continuous hinge 76mm open

Opening angle 270°. Other lengths and pin materials are available on request.

Specific drilling requirements are also available on request.

Hinge in raw galvanised steel is made of pregalvanised steel.

Therefore any cut surface is ungalvanised.

Α	В	C	D	E	note	material	finish	part number	pin material	weight
2160	76	1.5	4	15	undrilled	galvanised steel	raw	40-1-4681	brass	2400g
2160	76	1.5	4	15	undrilled	304 stainless steel	raw	42-1-4094	stainless steel	2400g

Rolled knuckle continuous hinge 80mm open

Opening angle 270°. Other lengths and pin materials are available on request. Specific drilling requirements are also available on request.

Α	В	С	D	Е	note	material	finish	part number	pin material	weight
2000	80	2	7.6	40	undrilled	steel	raw	40-1-3542	steel	3900g
2000	80	3	6	40	undrilled	steel	raw	40-1-4369	steel	5060g
1000	80	3	6	40	undrilled	304 stainless steel	raw	42-1-3304	stainless steel	2530g
2000	80	3	6	40	undrilled	304 stainless steel	raw	42-1-3569	stainless steel	5060g

