


- For cam
- For Profile cylinder
- Dust cover option
- IP65 Protection degree
- 90° Handle rotation
- Universal LH / RH



VISION™ SWING HANDLE FOR 40 mm OR 45 mm PROFILE CYLINDER

Low profile swing handle for 40 mm or 45 mm profile cylinder and cam.

Stainless version: Page 6-020.
Profile cylinders: Page 1-210.

Rod Latch System "Vision Classic": Page 1-008.51, 1-008.52 and 1-008.53.
Cut-out, version C: Page 1-001.01.

MATERIAL:
Handle and dish: Zinc, black texture powder coated or glass fibre reinforced polyamide (PA6), black.
Dust cover: TPE.
Shaft: Zinc die-cast, zinc plated.

MODEL: (see table below)
Turn-to-latch = The door is locked by turning the key.
T = For door thickness: 0,8-3,5 mm.
PDL = Spring loaded padlock loop retracts when handle is released.

Specifications subject to change without notice

VISION™ SWING HANDLE FOR 40 mm PROFILE CYLINDER (AAAAAABCD-EEEE)									
AAAAAA	Material	B	Opening rotation	C	T=	D	PDL	-EEEE	Dust cover
121611	Handle zinc / Dish PA6. X=28	1	90° clockwise or counter-clockwise	1	0,8-1,5	0	No	-C60U	No
121641	Handle zinc / Dish zinc. X=28	2	90° counter-clockwise	2	1,6-2,5			-C60D	Yes
125011	Handle PA6 / Dish PA6. X=28	3	90° clockwise	3	2,6-3,5				

VISION™ SWING HANDLE FOR 45 mm PROFILE CYLINDER (AAAAAABCD-EEEE)									
AAAAAA	Material	B	Opening rotation	C	T=	D	PDL	-EEEE	Dust cover
121611	Handle zinc / Dish PA6. X=33	1	90° clockwise or counter-clockwise	1	0,8-1,5	0	No	-C65U	No
121641	Handle zinc / Dish zinc. X=33	2	90° counter-clockwise	2	1,6-2,5			-C65D	Yes
		3	90° clockwise	3	2,6-3,5				