








VISION™

-  For cam
-  For BestLock cylinder
-  With padlock loop
-  Dust cover option
-  Protection degree
-  Handle rotation
-  Universal LH / RH



Specifications subject to change without notice

VISION™ SWING HANDLE FOR BESTLOCK CYLINDER

Low profile swing handle for BestLock cylinder and cam.

Rod Latch System "Vision Classic": Page 1-008.51, 1-008.52 and 1-008.53.
Cut-out, version C: Page 1-001.01.

MATERIAL:

Handle and dish: Zinc die-cast, black texture powder coated or glass fiber reinforced polyamide (PA6), black.
Dust cover: TPE.
Shaft: Zinc die-cast, zinc plated.
Padlock loop: Stainless steel (304).

MODEL: (see table below)

Turn-to-latch = The door is locked by turning the key.

T = For door thickness: 0,8-3,5 mm.

PDL = Spring loaded padlock loop retracts when handle is released.

VISION™ SWING HANDLE FOR BESTLOCK CYLINDER (AAAAABCD-EEEE)									
AAAAAA	Material	B	Opening rotation	C	T=	D	PDL	-EEEE	Dust cover
121611	Handle zinc / Dish PA6	1	90° clockwise or counter-clockwise	1	0,8-1,5	1	Yes	-C70U	No
121641	Handle zinc / Dish zinc	2	90° counter-clockwise	2	1,6-2,5			-C70D	Yes
		3	90° clockwise	3	2,6-3,5				