


- For control mechanism
- For Profile cylinder
- Dust cover option
- IP65 Protection degree
- 90° Handle rotation
- Universal LH / RH



VISION™ SWING HANDLE FOR 40 mm OR 45 mm PROFILE CYLINDER

Low profile swing handle for 40 mm or 45 mm profile cylinder and control mechanism.

Stainless version: Page 6-010.
Profile cylinders: Page 1-210.

Rod Latch Systems: Page 1-008.00 to 1-008.57.
Cut-out, version C: Page 1-001.01.

MATERIAL:

Handle and dish: Glass fibre reinforced polyamide (PA6), black or zinc, die-cast, black texture powder coated.
Dust cover: TPE.
Shaft: Zinc die-cast, zinc plated.

MODEL: (see table below)

Turn-to-latch = The door is locked by turning the key.

T = For door thickness: 0,8-3,5 mm.

PDL = Spring loaded padlock loop retracts when handle is released.

VISION™ SWING HANDLE FOR 40 mm PROFILE CYLINDER (AAAAAABC-DDDD)							
AAAAAAA	Material	B	T=	C	PDL	-DDDD	Dust cover
1216118	Handle zinc / Dish PA6. X=28	1	0,8-1,5	0	No	-C60U	No
1216418	Handle zinc / Dish zinc. X=28	2	1,6-2,5			-C60D	Yes
1250118	Handle PA6 / Dish PA6. X=28	3	2,6-3,5				

VISION™ SWING HANDLE FOR 45 mm PROFILE CYLINDER (AAAAAABC-DDDD)							
AAAAAAA	Material	B	T=	C	PDL	-DDDD	Dust cover
1216118	Handle zinc / Dish PA6. X=33	1	0,8-1,5	0	No	-C65U	No
1216418	Handle zinc / Dish Zinc. X=33	2	1,6-2,5			-C65D	Yes
		3	2,6-3,5				

Specifications subject to change without notice