









VISION™

-  For control mechanism
-  For BestLock cylinder
-  With padlock loop
-  Dust cover option
-  IP65 Protection degree
-  90° Handle rotation
-  Universal LH / RH



Specifications subject to change without notice

VISION™ SWING HANDLE FOR BESTLOCK CYLINDER

Low profile swing handle for BestLock cylinder and control mechanism.

Rod Latch Systems: Page 1-008.00 to 1-008.57.
Cut-out, version C: Page 1-001.01.

MATERIAL:

Handle and dish: Zinc die-cast, black texture powder coated or glass fibre reinforced polyamide (PA6), black.
Shaft: Zinc die-cast, zinc plated.
Padlock loop: Stainless steel (304).

MODEL: (see table below)

Turn-to-latch = The door is locked by turning the key.

T = For door thickness: 0,8-3,5 mm.

PDL = Spring loaded padlock loop retracts when handle is released.

VISION™ SWING HANDLE FOR BESTLOCK CYLINDER (AAAAAABC-DDDD)							
AAAAAA	Material	B	T=	C	PDL	-DDDD	Dust cover
1216118	Handle zinc / Dish PA6	1	0,8-1,5	1	Yes	-C70U	No
1216418	Handle zinc / Dish zinc	2	1,6-2,5			-C70D	Yes
		3	2,6-3,5				