



For cam



With insert



Padlock loop option



Protection degree



Handle rotation



Universal LH / RH

## VISION™ SWING HANDLE TOOL OPERATED

Low profile swing handle with insert for cam.

Rod Latch System "Vision Classic": Page 1-008.51, 1-008.52 and 1-008.53.

Keys: Page 2-370 and 2-372.

Cut-out, version C: Page 1-001.01.

Stainless version, see page 6-020.

### MATERIAL:

Handle and dish: Zinc die-cast, black texture powder coated or glass fibre reinforced polyamide (PA6), black.

Insert: Zinc die-cast, chrome plated.

Shaft: Zinc die-cast, zinc plated.

Padlock loop: Stainless steel (304).

### MODEL: (see table below)

Turn-to-latch = The door is locked by turning the key.

Push-to-latch = Spring loaded cam latches when the handle is pushed in.

T = For door thickness: 0,8-3,5 mm.

PDL = Spring loaded padlock loop retracts when handle is released.

### VISION™ SWING HANDLE TOOL OPERATED (AAAAABCD-EEEEF)

| AAAAAA | Material                | B | Opening rotation                   | C | T=      | D | PDL | -EEEE | Insert                    | F | Model         |
|--------|-------------------------|---|------------------------------------|---|---------|---|-----|-------|---------------------------|---|---------------|
| 121611 | Handle zinc / Dish PA6  | 1 | 90° clockwise or counter-clockwise | 1 | 0,8-1,5 | 0 | No  | -1301 | Hexagon 11                | 0 | Turn-to-latch |
| 121641 | Handle zinc / Dish zinc | 2 | 90° counter-clockwise              | 2 | 1,6-2,5 | 1 | Yes | -1308 | Square 7                  | 1 | Push-to-latch |
| 125011 | Handle PA6 / Dish PA6   | 3 | 90° clockwise                      | 3 | 2,6-3,5 |   |     | -1309 | Square 8                  |   |               |
|        |                         |   |                                    |   |         |   |     | -1312 | Triangular 7              |   |               |
|        |                         |   |                                    |   |         |   |     | -1313 | Triangular 8              |   |               |
|        |                         |   |                                    |   |         |   |     | -1316 | Double Bit 3              |   |               |
|        |                         |   |                                    |   |         |   |     | -1317 | Double Bit 5              |   |               |
|        |                         |   |                                    |   |         |   |     | -1347 | Recessed hex 8 / 3 mm pin |   |               |

Specifications subject to change without notice