



Specifications subject to change without notice



Universal LH / RH

## SYSTEM VISION™ INSIDE

Vision™ Inside latching system is mounted inside the sealed area and provide IP65 together with our Vision™ Swing handles. Latching points equipped with roller cams for smooth compression and latching. Multiple latching points for perfect sealing in tall applications. System with more than four latching points available upon request.

Control mechanism comes complete assembled with flat rod. Latching points ordered separately. Vision™ inside system can be equipped with additional standard cam on the control mechanism together with adapter (see table), for center latching point.

Handles: Page 1-002.01 /02 /03 /08, 1-004.03, and 1-006.01 /03.  
Cams: Page 2-481.

### MATERIAL:

Control mechanism: Zinc die-cast, zinc plated or special surface treatment\*.

Flat rod: Steel, zinc plated or stainless steel (316).

Roller cam and nut: Steel, zinc plated.

Roller and latching points: Glass fibre reinforced polyamide (PA6), black.

Adapter: Zinc die-cast, zinc plated.

\*30 day salt-spray test according to ISO 9227, equivalent to ASTM B 117.

VISION™ INSIDE ROD LATCH SYSTEM		
P/N Standard	P/N Highlander	Description
132110-A	139010-A	Roller cam
135010	135010	Latch point
13210600-2000	13900600-2000	Flat rod only. Length = 2000 mm
1302-00A1A2B1B2	1302-01A1A2B1B2	Control mechanism with pre-assembled flat rod
131116-05	-	Adapter for attaching standard cam on control mechanism
131116-07	-	Adapter for attaching roller cam on control mechanism

Specifications subject to change without notice