

VISION™



For cam



With insert




IP65 Protection degree



90° Handle rotation



Universal LH / RH



VISION™ COMPACT SWING HANDLE, TOOL OPERATED

Low profile compact swing handle with insert for cam.

Rod Latch System "Vision Classic": Page 1-008.51, 1-008.52 and 1-008.53.

Keys: Page 2-370 and 2-372.

Cut-out, version B: Page 1-001.01.

MATERIAL:

Handle: Zinc die-cast, black texture powder coated.
Dish: Glass fibre reinforced polyamide (PA6), black.
Insert: Zinc die-cast, chrome plated.
Shaft: Zinc die-cast, zinc plated.

MODEL: (See table below.)

Push-to-latch = Spring loaded cam latches when the handle is pushed in.

T = For door thickness: 0,8-3,5 mm.

PDL = Spring loaded padlock loop retracts when handle is released.

VISION™ COMPACT SWING HANDLE, TOOL OPERATED (AAAAABCD-EEEEF)											
AAAAA	Material	B	Opening rotation	C	T=	D	PDL	-EEEE	Insert	F	Model
141611	Handle zinc / Dish PA6	1	90° clockwise or counter-clockwise	1	0,8-1,5	0	No	-1301	Hexagon 11	1	Push-to-latch
		2	90° counter-clockwise	2	1,6-2,5			-1308	Square 7		
		3	90° clockwise	3	2,6-3,5			-1309	Square 8		
								-1312	Triangle 7		
								-1313	Triangle 8		
								-1316	Double Bit 3		
								-1317	Double Bit 5		
								-1347	Insex 8 / 3 mm pin		

Specifications subject to change without notice