



IP54 Protection degree

Universal LH / RH



CYLINDER LOCK 18 - 56,5 mm

Quarter-turn cylinder lock. Universal clockwise or counter-clockwise rotation when opening / closing. Supplied with nut. Protection degree IP54.

Cams with projection: 2-480 and 2-490 - cam rotates 90° and the key can be removed in the locked position.
Cams without projection: 2-481 and 2-491 - cam rotates 180° and the key can be removed in both open and locked position.

Supplied with two keys.

The master key system (marked with *) is supplied on request only.

MATERIAL:

Housing: Zinc die-cast, chrome plated or black texture powder coated.
Cylinder: Zinc die-cast, stainless steel cap and dust shutter.
Nut: Zinc die-cast, zinc plated.
Screw: Steel, zinc plated.

CYLINDER LOCK 18 - 56,5 mm				
P/N, Chrome	P/N, Black	Cylinder	Nut	Drawing
241334	241534	Keyed alike, IL 101	Standard	A
241335	241535	Keyed alike, IL 101	Earthing nut	A
241336	241536	Keyed to differ	Standard	A
241337	241539	Keyed to differ	Earthing nut	A
241336-HNS*	241536-HNS*	Master key system*	Standard	A
241356	241556	Keyed alike, IL 101	Standard	B
241358	241558	Keyed alike, IL 101	Earthing nut	B
241357	241557	Keyed to differ	Standard	B
241359	241559	Keyed to differ	Earthing nut	B
241357-HNS	241557-HNS	Master key system	Standard	B

Specifications subject to change without notice