



Protection degree



Universal LH / RH

## COMPRESSION LATCH - 35 mm



Compression latch. Close and tighten with a single continuous half-turn motion. First 90° turn moves the cam 90°, the second 90° turn retracts the cam 6 mm. The latch is supplied assembled, cam to be ordered separately. Protection degree IP65.

Stainless version: Page 6-135.  
Other inserts on request.

QUARTER-TURN - 35 mm		
P/N Chrome	P/N Black	Insert
241387-01	241587-01	Hexagon 11
241387-09	241587-09	Square 8
241387-11	241587-11	Square 8 / M6 *
241387-12	241587-12	Triangle 7
241387-13	241587-13	Triangle 8
241387-14	241587-14	Triangle 10
241387-15	241587-15	Triangle 10 / M6
241387-16	241587-16	Double Bit 3
241387-17	241587-17	Double Bit 5
241387-20	241587-20	Slotted
241387-21	241587-21	Recessed hexagon 10
241387-22	241587-22	Recessed hexagon 8
241387-28	241587-28	Triangle 10/M5
241387-47	241587-47	Recessed hexagon 8 / 3 mm pin
241387-56	241587-56	Tubular Asymmetric
241387-79	241587-79	Triangle 6,5

Specifications subject to change without notice