



IP65 Protection degree

 Universal LH / RH

QUARTER-TURN L-HANDLE - 18 mm



Quarter-turn L-handle in locking or non-locking version. Universal clockwise or counter-clockwise rotation when opening / closing. Supplied with mounting nut and two keys. Protection degree IP65.

Key extraction: Open / closed.
Stainless version: Page 6-160.

* Master key system on request.

Cams: Page 2-480, 2-490 and 2-510.
Rods: Page 2-540, 2-541 and 2-545.

MATERIAL:

Housing and handle: Zinc die-cast, chrome plated or black coated.
Cylinder: Zinc die-cast, stainless steel (304) cap and dust shutter.
Standard and Earthing nut: Zinc die-cast, zinc plated.
Screw: Steel, zinc plated.

QUARTER-TURN L-HANDLE - 18 mm			
P/N	Cylinder	Surface treatment	Nut
261356	Non-locking	Chrome	Standard
261357	Non-locking	Chrome	Earthing nut
261556	Non-locking	Black	Standard
261557	Non-locking	Black	Earthing nut
261358	Keyed alike IL101	Chrome	Standard
261359	Keyed alike IL101	Chrome	Earthing nut
261558	Keyed alike IL101	Black	Standard
261559	Keyed alike IL101	Black	Earthing nut
261369	Keyed alike IL0333	Chrome	Standard
261370	Keyed alike IL0333	Chrome	Earthing nut
261569	Keyed alike IL0333	Black	Standard
261570	Keyed alike IL0333	Black	Earthing nut
261360	Keyed to differ *	Chrome	Standard
261361	Keyed to differ *	Chrome	Earthing nut
261560	Keyed to differ *	Black	Standard
261561	Keyed to differ *	Black	Earthing nut

Specifications subject to change without notice