



IP65 Protection degree

 Padlock loop

 Universal LH / RH

PADLOCKABLE DEFEATER HANDLE - 58 mm

Padlockable def eater handle equipped with a built-in spring loaded insert, providing a def eater function making the handle compliant with two-handed safety operations requirements. To operate the handle, turn the insert, push the padlock trigger and turn the handle. The cast-in threaded steel shaft allows simple cam adjustment. Removable stop for clockwise or counter-clockwise operation. Supplied with nut, screws and gasket. Protection degree IP65. Cut-out is "Combi"-style, with an additional $\varnothing 8,5$ mm hole.

Products marked with * are key-locking and are supplied with two keys.
Key extraction: Closed.

Stainless compact def eater handle: Page 6-210.

Cams: 12 mm square cut-out, supplied on request.

Rods: Page 2-540, 2-541 and 2-545.

Keys: Page 2-370 and 2-372.

MATERIAL:

Handle: Zinc die-cast, black texture powder coated.

Insert and padlock trigger: Zinc die-cast, chrome plated.

Nut: Zinc die-cast, zinc plated.

Screws: Steel zinc plated.

Cast-in shaft: Hardened steel, zinc plated.

Gaskets: Plastic and NBR.

PADLOCKABLE DEFEATER HANDLE - 58 mm			
P/N	Insert	P/N	Insert
261601-01	Hexagon 11	261601-20	Slotted
261601-07	Square 6	261601-21	Recessed hexagon 10
261601-08	Square 7	261601-22	Recessed hexagon 8
261601-09	Square 8	261601-23	Hexagon 8,5
261601-10	Square 8 /slotted	261601-24	ES3
261601-11	Square 8 / M6	261601-28	Triangle 10 / M5
261601-12	Triangle 7	261601-41	Slotted recessed
261601-13	Triangle 8	261601-47	Recessed hexagon 8 / 3 mm pin
261601-14	Triangle 10	261601-48	Recessed square 8.
261601-15	Triangle 10 / M6	261601-49	Slotted 3 mm
261601-16	Double Bit 3	261602-10	Cylinder lock keyed alike (IL101) *
261601-17	Double Bit 5	261602-20	Cylinder lock keyed to differ *
261601-18	Daimler Benz	261603	Solid plug. No def eater - only padlock trigger
261601-19	Triangle 10 / SEN		

Specifications subject to change without notice