



Padlock loop



Universal LH / RH

PADLOCKABLE COMPRESSION HANDLE TOOL OPERATED 36 - 56 mm

Padlockable compression handle with insert and 6 mm compression stroke. Spring loaded padlock loop retracts when not in use. Mounting: Rivets/screws (not included). The C-dimension is the compressed position.

Suitable for cams with or without projection: Page 2-480, 2-481, 2-490 and 2-491.

Keys: Page 2-370 and 2-372.

MATERIAL:

Handle: Glass fibre reinforced polyamide (PA6), black.

Housing: Zinc, die-cast, black texture powder coated.

Insert, pin and padlock loop: Zinc die-cast, black passivated.

Screw: Steel, zinc plated.

Example: Handle for C=46 with insert "Double Bit 3" = P/N 27501140-1216.

CREATE P/N FOR PADLOCKABLE COMPRESSION HANDLE TOOL OPERATED 36 - 56 mm (AAAAAABB-CCCC)

AAAAAA	Description	BB	C=	-CCCC	Insert
275011	Handle	30	36	-1201	Hexagon 11
		40	46	-1207	Square 6
		50	56	-1208	Square 7
				-1209	Square 8
				-1210	Square 8 / slotted
				-1212	Triangle 7
				-1213	Triangle 8
				-1214	Triangle 10
				-1216	Double Bit 3
				-1217	Double Bit 5
				-1218	Daimler Benz
				-1219	Triangle 10 / SEN
				-1220	Slotted
				-1221	Recessed hexagon 10
				-1222	Recessed hexagon 8
				-1223	Hexagon 8,5
				-1224	ES3
				-1241	Slotted recessed
				-1247	Recessed hexagon 8 / 3 mm pin
				-1248	Slotted recessed square 8