




-  120° Opening angle
-  Universal LH / RH
-  Lift-off

VISION™ CONCEALED HINGE - 120° OPENING ANGLE WITH CLICK FUNCTION. 40 mm HOLE SPACING

Concealed hinge with a patented function that enables the door part to be engaged to, or separated from, the frame part with a "click". Easy door assembly by placing the door in the frame parts and close. The door part and frame part snap together. Secure the hinge by activating the red safety catch. Screw mounted frame part. The door part is mounted on weld-on studs. Universal right and left mounting. Opening angle 120°.

| VISION™ CONCEALED CLICK-HINGE - 40 mm HOLE SPACING | |
|----------------------------------------------------|----------------|
| P/N Standard | P/N Highlander |
| 311117 | 311417 |

Vision™ system components: Chapter 1.

MATERIAL:

Standard design:
 Frame part: Steel, zinc plated.
 Pin: Stainless steel (303).
 Washer: Brass.
 Door part: Zinc die-cast, zinc plated.
 Red safety catch: Glass fiber reinforced polyamide (PA6), red.

Highlander design:

Frame part and pin: Stainless steel (303).
 Washer: Brass.
 Door part: Zinc die-cast, special surface treatment *.
 Red safety catch: Glass fiber reinforced polyamide (PA6), red.

* 30 day salt-spray test according to ISO 9227, equivalent to ASTM B 117.

Specifications subject to change without notice