















SEALING PROFILES

Self-gripping profile with EPDM-rubber carrier and sealing lip and / or sealing tube from sponge-rubber. Integrated steel strip core or steel wire core (see table). Products that are UL-recognized are indicated in the UL-column below. Products marked with ¹ are supplied in UL 94 HB-version.

SEALING PROFILES							
Drawing	P/N	Description	UL	Colour	Clamping range in mm	Bending radius in mm	Coil size
	427010 ¹	Steel strip core.		Black	1,0-3,5	A=200, B=80, C=200, D=200	50 m
	427020-04 ¹	Steel strip core.		Black	2,0-4,0	A=80, B=80, C=-, D=-	75 m
	427020-06 ¹	Steel strip core.		Black	5,0-6,0	A=80, B=80, C=-, D=-	75 m
	427033 ¹	Steel wire core.		Black	1,0-3,0	A=80, B=40, C=200, D=180	3x50 m
	427038-04 ¹	Steel strip core.		Black	2,0-4,0	A=80, B=120, C=-, D=-	3x25 m
	427038-06 ¹	Steel strip core.		Black	4,0-6,0	A=80, B=120, C=-, D=-	3x25 m
	427042 ¹	Steel wire core.		Black	1,5-3,0	A=80, B=60, C=200, D=80	4x25 m
	427068	Steel wire core.		Black	3,0-5,0	-	75 m

Specifications subject to change without notice