














SEALING PROFILES

Self-gripping sealing profile with a black EPDM rubber carrier and a sealing lip and / or sealing tube from sponge-rubber. Integrated steel strip core or steel wire core (see table).

P/N 427009 NBR is made of nitrile rubber. Products that are UL-recognized are indicated in the UL-column below. Products marked with ¹ are supplied in UL 94 HB-version.

SEALING PROFILES							
Drawing	P/N	Description	UL	Colour	Clamping range in mm	Bending radius in mm	Coil size
	427009 ¹	With steel wire core		Black	1,0-3,0	A=50, B=180, C=30, D=30	2 x 50 m
	427009 NBR	With steel wire core	No	Black	1,0-3,0	A=50, B=180, C=30, D=30	2 x 50 m
	427021 ¹	With steel wire core		Black	0,5 - 1,5	A=50, B=80, C=25, D=25	2 x 50 m
	427029-02 ¹	With steel wire core		Black	1,0-2,5	A=100, B=180, C=25, D=25	2 x 50 m
	427029-04 ¹	With steel wire core		Black	2,5-4,0	A=100, B=180, C=25, D=25	2x50 m
	427030 ¹	With steel strip core		Black	1,0-2,5	A=60, B=120, C=25, D=25	100 m
	427040 ¹	With steel wire core		Black	1,0-2,0	A=50, B=60, C=20, D=20	2 x 50 m
	427043 ¹	With steel wire core		Black	1,0-3,0	A=50, B=200, C=25, D=25	50 m

Specifications subject to change without notice