













## SEALING PROFILES

Self-gripping profile with EPDM-rubber carrier and sealing lip and / or sealing tube from sponge-rubber. Integrated steel wire core. Products that are UL-recognized are indicated in the UL-column below.

Products marked with <sup>1</sup> are supplied in UL 94 HB-version.

SEALING PROFILES							
Drawing	P/N	Description	UL	Colour	Clamping range in mm	Bending radius in mm	Coil size
	427008 <sup>1</sup>	With steel wire core.		Black	2,0	A=50, B=20, C=120, D=40	2 x 50 m
	427008 NBR	With steel wire core.	No	Black	2,0	A=50, B=20, C=120, D=40	2 x 50 m
	427026 <sup>1</sup>	With steel wire core.		Black	1,0-2,5	A=20, B=50, C=20, D=60	100 m
	427031 <sup>1</sup>	With steel wire core.		Black	0,8-2,5	A=40, B=40, C=100, D=60	2 x 50 m
	427032 <sup>1</sup>	With steel wire core.		Black	2,0	A=30, B=40, C=30, D=60	2 x 50 m
	427052 <sup>1</sup>	With steel wire core.		Black	1,0-2,0	A=100, B=200, C=100, D=60	100 m
	427007	With steel wire core.		Black	2,0	A=20, B=50, C=20, D=60	50 m

Specifications subject to change without notice